


Poz cija	Daudz.	Apraksts
	1	<p>ALPHA2 25-40 180</p>  <p>Izstr d juma Nr.: 97704990</p> <ul style="list-style-type: none"> • AUTOADAPT function automatically finds the best setpoint and thus reduces the energy consumption and setup time. • Insulating shells are supplied with pumps to minimise ENERGY heat loss in heating and cooling systems. • A display shows the actual power consumption in Watt or actual flow rate in m³/h for control purposes. • The best energy efficiency index (EEI) in the market provides the highest energy savings during a year. • Stainless-steel pump housings are available if the application demand corrosion resistance or for drinking water, DHW applications. • Complies with the German regulation for energy saving in buildings and building systems, Energieeinsparverordnung – EnEV §14(3). • Automatic night setback function that further reduces the energy consumption if the boiler provides this feature. • Simple selection among three constant-pressure curves, three proportional-pressure curves or three fixed speeds with only one button . Quick and simple setup. • ALPHA plug. Easy, quick and safe electrical connection. • ALPHA2 is suitable for cold-water systems, drinking water approval. High application flexibility . • Electro-coated pump housing. • No external motor protection is required. Reduced installation time and costs. • New improved start. Secure start under tough conditions. • New advanced. Dry- running protection. Protects the pump at initial start-up and daily operation if there is no water in the pump. • Manual summer mode. Saves energy during the summertime –consumption <0,8W and ensures safe start at the next heating season. <p>Š idrums:</p> <p>S kn jamais š idrums: Apkures dens</p> <p>Š idruma temperat ras diapazons: 2 .. 110 °C</p> <p>Liquid temp: 60 °C</p> <p>Bl vums: 983.2 kg/m³</p> <p>Kinem tisk viskozit te: 1 mm²/s</p> <p>Technical:</p> <p>Faktiski apr in t pl sma: 0.5091 l/s</p> <p>S k a rezult jošais s kn šanas augstums: 15.68 kPa</p> <p>TF klase: 110</p> <p>Apstiprin jumi pases datu pl ksn t : VDE,GS,CE</p> <p>Materi li:</p> <p>S k a korpuss: uguns</p> <p>EN-GJL-150</p> <p>ASTM A48-150B</p> <p>S k rats: PES 30%GF</p>

Pozīcija	Daudz.	Apraksts
		<p>Uzstādīšana:</p> <p>Apkārtojuma vidējās temperatūras diapazons: 0 .. 40 °C</p> <p>Maks. darba spiediens: 1000 kPa</p> <p>Pievienojums: G 1 1/2</p> <p>Spiediena pakāpe: PN 10</p> <p>Garums no viena pievienojuma līdz otram: 180 mm</p> <p>Elektriskie dati:</p> <p>Īstās jauda P1: 3 .. 18 W</p> <p>Tīkla frekvence: 60 Hz</p> <p>Nominālā spriegums: 1 x 230 V</p> <p>Maksimālā strāvas patēriņš: 0.04 .. 0.18 A</p> <p>Korpusa klase (IEC 34-5): X4D</p> <p>Izolācijas klase (IEC 85): F</p> <p>Citi:</p> <p>Energy (EEI): 0.15</p> <p>Neto svars: 2.01 kg</p> <p>Bruto svars: 2.13 kg</p> <p>Piegādes tilpums: 0.004 m³</p>