


Poz cija	Daudz.	Apraksts
	1	<p>ALPHA2 25-50 180</p>  <p>Izstr d juma Nr.: 97993200</p> <ul style="list-style-type: none"> • AUTOADAPT function automatically finds the best setpoint and thus reduces the energy consumption and setup time. • Insulating shells are supplied with pumps to minimise ENERGY heat loss in heating and cooling systems. • A display shows the actual power consumption in Watt or actual flow rate in m³/h for control purposes. • The best energy efficiency index (EEI) in the market provides the highest energy savings during a year. • Stainless-steel pump housings are available if the application demand corrosion resistance or for drinking water, DHW applications. • Complies with the German regulation for energy saving in buildings and building systems, Energieeinsparverordnung – EnEV §14(3). • Automatic night setback function that further reduces the energy consumption if the boiler provides this feature. • Simple selection among three constant-pressure curves, three proportional-pressure curves or three fixed speeds with only one button . Quick and simple setup. • ALPHA plug. Easy, quick and safe electrical connection. • ALPHA2 is suitable for cold-water systems, drinking water approval. High application flexibility . • Electro-coated pump housing. • No external motor protection is required. Reduced installation time and costs. • New improved start. Secure start under tough conditions. • New advanced. Dry- running protection. Protects the pump at initial start-up and daily operation if there is no water in the pump. • Manual summer mode. Saves energy during the summertime –consumption <0,8W and ensures safe start at the next heating season. <p>Š idrums:</p> <p>S kn jamais š idrums: Apkures dens</p> <p>Š idruma temperat ras diapazons: 2 .. 110 °C</p> <p>Liquid temp: 80 °C</p> <p>Bl vums: 971.8 kg/m³</p> <p>Kinem tisk viskozit te: 1 mm²/s</p> <p>Technical:</p> <p>Faktiski apr in t pl sma: 0.31 l/s</p> <p>S k a rezult jošais s kn šanas augstums: 30 kPa</p> <p>TF klase: 110</p> <p>Apstiprin jumi pases datu pl ksn t : VDE,GS,CE</p> <p>Materi li:</p> <p>S k a korpuss: uguns</p> <p>EN-GJL-150</p> <p>ASTM A48-150B</p> <p>S k rats: PES 30%GF</p>

Poz cija	Daudz.	Apraksts
		Uzst d šana: Apk rt j s vides temperat ras diapazons: 0 .. 40 °C Maks. darba spiediens: 10 bar Pievienojums: G 1 1/2 Spiediena pak pe: PN 10 Garums no viena pievienojuma l dz otram: 180 mm Elektriskie dati: Ieejas jauda P1: 3 .. 26 W T kla frekvence: 60 Hz Nomin lais spriegums: 1 x 230 V Maksim lais str vas pat ri š: 0.04 .. 0.24 A Korpusa klase (IEC 34-5): X4D Izol cijas klase (IEC 85): F Citi: Energy (EEI): 0.16 Neto svars: 2.01 kg Bruto svars: 2.13 kg Pieg des tilpums: 0.004 m ³